



Temperatura:  
-20°C  
+120°C DIN  
4109

| DN   | D      | L       | e   | b  | M   | Unidad<br>Caja | Peso<br>kg/u. |
|------|--------|---------|-----|----|-----|----------------|---------------|
|      | mm     | mm      | mm  | mm |     |                |               |
| 15   | 15-18  | 58      | 2,5 | 20 | M8  | 50             | 0,062         |
| 18   | 3/8"   | 16-18   | 2,5 | 20 | M8  | 50             | 0,062         |
| 22   | 1/2"   | 20-24   | 2,5 | 20 | M8  | 50             | 0,075         |
| 28   | 3/4"   | 25-28   | 2,5 | 20 | M8  | 50             | 0,084         |
| 35   | 1"     | 31-35   | 2,5 | 20 | M8  | 50             | 0,102         |
| 42   | 1.1/4" | 39-43   | 2,5 | 20 | M8  | 50             | 0,106         |
| 54   | 1.1/2" | 47-54   | 2,5 | 20 | M8  | 50             | 0,130         |
|      | 2"     | 58-61   | 2,5 | 20 | M8  | 20             | 0,145         |
| 76,1 | 2.1/2" | 73-76,5 | 2,5 | 30 | M10 | 10             | 0,142         |
| 88,9 | 3"     | 86-89   | 2,5 | 30 | M10 | 10             | 0,164         |
|      | 4"     | 110-115 | 2,5 | 30 | M10 | 10             | 0,206         |