

SPIRALI IN POLIAMIDE SENZA CODOLI

POLYAMIDE RECOIL TUBING WITHOUT TAIL
 SPIRALROHRE AUS POLYAMID OHNE GERADE ENDEN
 TUBE SPIRALÉ EN POLYAMIDE SANS EXTRÉMITÉS DROITES
 ESPIRALES EN POLIAMIDA SIN TERMINALES
 ESPIRAIS DE POLIAMIDA SEM ABAS

SS12

SPIRALE IN POLIAMIDE SENZA CODOLI

POLYAMIDE RECOIL TUBING WITHOUT TAIL

SPIRALROHRE AUS POLYAMID OHNE GERADE ENDEN

TUBE SPIRALÉ EN POLYAMIDE SANS EXTRÉMITÉS DROITES

ESPIRAL EN POLIAMIDA SIN TERMINALES

ESPIRAIS DE POLIAMIDA SEM ABAS



Code	Colore Color Farbe Couleur Color Cor	Est.	Int.	Ø Est.	Lunghezza Lineare Linear Length Gerade Länge Longueur Étirée Longitud Lineal Comprimento Linear	Pressione d'esercizio Working pressure Betriebsdruck Pression de travail Presión de ejercicio Pressão de trabalho	Pressione di scoppio Burst pressure Berstdruck Pression d'éclatement Presión de rotura Pressão de ruptura	Tolleranza Tolerance Toleranz Tolérance Tolerancia Tolerância	Pack.
		mm	mm	mm	Mt	a/at 20°C bar	a/at 20°C bar	mm	
SS12 0064 030	BL	6	4	63	30	27	81	± 0.10	1
SS12 0086 030	BL	8	6	87	30	20	60	± 0.10	1
SS12 0108 030	BL	10	8	106	30	15	45	± 0.12	1
SS12 0121 030	BL	12	10	135	30	13	39	± 0.15	1



Temperatura d'uso

Temperature Range

Temperaturbereich

Température d'utilisation

Temperatura de Ejercicio

Temperatura de Trabalho

- 40 °C

+ 70 °C



Tabella delle pressioni espresse in % in funzione della temperatura
 Table of pressure values expressed in % as a function of temperature
 Tabelle In Abhängigkeit Der Temperaturen Die Druckwerte In % Angegeben
 Valeurs de pression (en %) en fonction de la température
 Tabla de las presiones expresadas en % en función de la temperatura
 Tabela das pressões expressas em % em função da temperatura

-20°	0°	20°	30°	40°	50°	60°	70°
180%	140%	100%	90%	80%	70%	60%	50%

SPIRALI IN POLIURETANO POLIETERE 95 SHORE A CON CODOLI

POLYURETHANE POLYETHER 95 SHORE RECOIL TUBING WITH TAILS
 SPIRALROHRE AUS POLYURETHAN-POLYETHER 95 SHORE A MIT GERADEN ENDEN
 TUBE SPIRALÉ EN POLYURÉTHANE POLYÉTHÉR 95 SHORE A
 ESPIRALES EN POLIURETANO POLIÉTER 95 SHORE A CON TERMINALES
 ESPIRAIS DE POLIURETANO POLIÉTER 95 SHORE A COM ABAS

SDPU

SPIRALE IN POLIURETANO POLIETERE 95 SHORE A CON CODOLI

POLYURETHANE POLYETHER 95 SHORE RECOIL TUBING WITH TAILS
 SPIRALROHRE AUS POLYURETHAN-POLYETHER 95 SHORE A MIT GERADEN ENDEN
 TUBE SPIRALÉ EN POLYURÉTHANE POLYÉTHÉR 95 SHORE A AVEC EXTRÉMITÉS DROITES
 ESPIRAL EN POLIURETANO POLIÉTER 95 SHORE A CON TERMINALES
 ESPIRAL DE POLIURETANO POLIÉTER 95 SHORE A COM ABAS

Misura Size Größe Dimensions Tamanho	1	2
	mm	
6 - 4	100	100
8 - 5.5	120	500
10 - 6.5	120	500
12 - 8	120	500



Code	Colore Color Farbe Couleur Cor	Est.	Int.	Ø Est.	Lunghezza Lineare Linear lenght Gerade Länge Longueur étirée Longitud lineal Comprimento linear	Lunghezza a riposo Stowed lenght Blocklänge Longueur des spires jointes Longitud en reposo Comprimento em repouso	Lunghezza di Esercizio Working lenght Arbeitslänge Longueur de travail Longitud de ejercicio Comprimento de trabalho	Pressione d'esercizio Working pressure Betriebsdruck Pression de travail Presión de ejercicio Pressão de trabalho	Pressione di scoppio Burst pressure Berstdruck Pression d'éclatement Presión de rotura Pressão de ruptura	Tolleranza Tolerance Toleranz Tolérance Tolerancia Tolerância	Pack.
		mm	mm	mm	Mt	a/at 23°C mm	a/at 23°C Mt	a/at 20°C bar	bar	mm	
SDPU 0064 004	AZ	6	4	32	4	325	3	11	32	± 0.10	1
SDPU 0085 505	AZ	8	5.5	41	5	410	4	10	30	± 0.10	1
SDPU 0106 505	AZ	10	6.5	60	5	330	4	11	33	± 0.12	1
SDPU 0120 805	AZ	12	8	80	5	305	3	11	32	± 0.15	1
SDPU 0085 075	AZ	8	5.5	41	7.5	660	6	10	30	± 0.10	1
SDPU 0106 575	AZ	10	6.5	60	7.5	500	6	11	33	± 0.12	1
SDPU 0120 875	AZ	12	8	80	7.5	430	6	11	32	± 0.15	1



Temperatura d'uso

Temperature Range

Temperaturbereich

Température d'utilisation

Temperatura de Ejercicio

Temperatura de Trabalho

- 40 °C

+ 60 °C



Tabella delle pressioni espresse in % in funzione della temperatura
 Table of pressure values expressed in % as a function of temperature
 Tabelle in Abhängigkeit Der Temperaturen Die Druckwerte in % Angegeben
 Valeurs de pression (en %) en fonction de la température
 Tabla de las presiones expresadas en % en función de la temperatura
 Tabela das pressões expressas em % em função da temperatura

-20°	0°	20°	30°	40°	50°	60°
110%	100%	100%	85%	70%	60%	50%

KIT SOFFIAGGIO

BLOWER KIT
GEBLÄSE-KIT
KIT SOUFFLETTE
KIT DE VENTILADOR
KIT VENTILADOR



Temperatura d'uso

Temperature Range

Temperaturbereich

Température d'utilisation

Temperatura de Ejercicio

Temperatura de Trabalho

- 40 °C

+ 60 °C



Tabella delle pressioni espresse in % in funzione della temperatura
Table of pressure values expressed in % as a function of temperature
Tabelle In Abhängigkeit Der Temperaturen Die Druckwerte In % Angegeben
Valeurs de pression (en %) en fonction de la température
Tabla de las presiones expresadas en % en función de la temperatura
Tabela das pressões expressas em % em função da temperatura

-20°	0°	20°	30°	40°	50°	60°
110%	100%	100%	85%	70%	60%	50%

SK001

SPIRALE IN POLIURETANO POLIETERE 95 SHORE A CON RACCORDO DIRITTO ORIENTABILE MASCHIO CILINDRICO

POLYURETHANE POLYETHER 95 SHORE A RECOIL TUBING WITH BSPP SWIVEL STRAIGHT MALE ADAPTOR

SPIRALROHRE AUS POLYURETHAN-POLYETHER 95 SHORE A MIT GERADE EINSCHRAUBVERSCHRAUBUNG ZYLINDRISCH (DREHBAR)

TUBE SPIRALÉ EN POLYURÉTHANE POLYÉTHÉR 95 SHORE A AVEC RACCORD ORIENTABLE DROIT MÂLE CYLINDRIQUE

ESPIRAL EN POLIURETANO POLIÉTER 95 SHORE A CON RACOR RECTO ORIENTABLE MACHO CILÍNDRICO CON TÓRICA

ESPIRAL DE POLIURETANO POLIÉTER 95 SHORE A COM CONEXÃO RETA MACHO ORIENTÁVEL COM ROSCA PARALELA




Code	Colore Color Farbe Couleur Color Cor	Ø Int.	Ø Est.	Lunghezza Lineare Linear lenght Gerade Länge Longueur étirée Longitud lineal Comprimento linear	Filettatura Threads Gewindearten Filetages Roscas Roscas	Pack.
		mm	mm	Mt		
SK001 0640 02	AZ	4	6	2	1/4	1
SK001 0855 05	AZ	5.5	8	5	1/4	1
SK001 0855 75	AZ	5.5	8	7.5	1/4	1
SK001 1065 75	AZ	6.5	10	7.5	1/4	1
SK002 1208 75	AZ	8	12	7.5	3/8	1

SK010

SPIRALE IN POLIURETANO POLIETERE 95 SHORE A CON PISTOLE DI SOFFIAGGIO

POLYURETHANE POLYETHER 95 SHORE A RECOIL TUBING WITH BLOW GUN
 SPIRALROHRE AUS POLYURETHAN-POLYETHER 95 SHORE A MIT BLASPISTOLEN
 TUBE SPIRALÉ EN POLYURÉTHANE POLYÉTHÉR 95 SHORE A AVEC SOUFFLETES
 ESPIRAL EN POLIURETANO POLIÉTER 95 SHORE A CON PISTOLAS SOPLADORAS
 ESPIRAL DE POLIURETANO POLIÉTER 95 SHORE A COM PISTOLA DE AR




Code	Colore Color Farbe Couleur Color Cor	Ø Int.	Ø Est.	L	Lunghezza Lineare Linear lenght Gerade Länge Longueur étirée Longitud lineal Comprimento lineal	Filettatura Threads Gewindearten Filetages Roscas Roscas	Pack.
		mm	mm	mm	Mt		
SK010 0855 05	AZ	5.5	8	90	5	1/4	1

SK022

SPIRALE IN POLIURETANO POLIETERE 95 SHORE A CON PISTOLE DI SOFFIAGGIO 362

POLYURETHANE POLYETHER 95 SHORE A RECOIL TUBING WITH 362 BLOW GUN
 SPIRALROHRE AUS POLYURETHAN-POLYETHER 95 SHORE A MIT BLASPISTOLEN 362
 TUBE SPIRALÉ EN POLYURÉTHANE POLYÉTHÉR 95 SHORE A AVEC SOUFFLETES 362
 ESPIRAL EN POLIURETANO POLIÉTER 95 SHORE A CON PISTOLAS SOPLADORAS 362
 ESPIRAL DE POLIURETANO POLIÉTER 95 SHORE A COM PISTOLA DE AR 362



Code	Colore Color Farbe Couleur Color Cor	Ø Int.	Ø Est.	L	L1	B	Lunghezza Lineare Linear lenght Gerade Länge Longueur étirée Longitud lineal Comprimento lineal	Filettatura Threads Gewindearten Filetages Roscas Roscas	Pack.
		mm	mm	mm	mm	mm	Mt		
SK022 0855 05	NE	5.5	8	90	210.5	179	5	1/4	1